COLD COLOR-CHANGING VINYL INSTRUCTION

Introduction

Cold color-changing vinyl can turn its original color into another when the temperature drops.

It can be applied to any smooth surface indoors and outdoors and remain sticky for a long time.

Instructions

- 1.Create your design. (No need to mirror it.)
- 2.Cut the design.
- 3.Weed the design. (For small letters and patterns, please press the part you need in case of being lifted when weeding.)
- 4. Use transfer tape to apply the design. (Squeegee the tape onto the vinyl.)
- 5.Peel off the vinvl.
- 6. Apply the vinyl to a clean and smooth surface.
- 7. Squeegee the vinyl.
- 8. Remove the transfer tape.
- 9 Finish

Ouick Reference Chart

| Cutting | | |
|---------|--|---|
| Cutter | Cricut | Silhoutte |
| Setting | Blade: Standard Setting: Holographic Sparkle Vinyl Pressure: Default | Vinyl Reflective (Blade: 8 Force:5/6 Speed: 5 Passes: 2) |

NOTE:

- 1. Please ensure the real vinyl is facing up when you cut the design.
- 2.The cutting parameters may vary depending on the condition of the blade and the age of the machine.
- 3. Please confirm that the blade is sharp enough and there is no scrap on the blade.

(This chart refers to the product's most suitable parameters for some third-party machines.)

Attention

- 1.The vinyl temperature needs to be reach 15°C(59°F) to change color.
- 2. Suitable for metal glass, plastic, ceramic, paper, smooth wall.
- 3. Not suitable for uneven surfaces, powdered walls damp walls and object surfaces.
- 4. Not suitable for clothing and other textiles.

Warm Tips

- 1. Store in a cool and dry area without direct sunlight.
- 2.Do not rinse the vinyl sheet with water within 24 hours after pasting.
- 3. Avoid strong acid and alkali corrosion.

Customer Service

Feel free to contact us if you have any questions or concerns.

Web: www.loklik.com