

# HOT COLOR-CHANGING VINYL INSTRUCTION

## Introduction

Hot color-changing vinyl can turn its original color into another when the temperature rises.

It can be applied to any smooth surface indoors and outdoors and remain sticky for a long time. No cheap backing ruining and separating from adhesive vinyl in the cutting process.

## Instructions

- 1.Create your design. (No need to mirror it.)
- 2.Cut the design.
- 3 Weed the design. (For small letters and patterns, please press the part you need in case of being lifted when weeding.)
- 4.Use transfer tape to apply the design. (Squeegee the tape onto the vinyl.)
- 5.Peel off the vinyl.
- 6.Apply the vinyl to a clean and smooth surface.
- 7.Squeegee the vinyl.
- 8.Remove the transfer tape.
- 9.Finish.

## Quick Reference Chart

Cutting		
Cutter	Cricut	Silhouette
Setting	Blade: Standard Setting: Holographic Sparkle Vinyl Pressure: Default	Vinyl Reflective (Blade: 8 Force:5/6 Speed: 5 Passes: 2)
<b>NOTE:</b> 1.Please ensure the real vinyl is facing up when you cut the design. 2.The cutting parameters may vary depending on the condition of the blade and the age of the machine. 3.Please confirm that the blade is sharp enough and there is no scrap on the blade. (This chart refers to the product's most suitable parameters for some third-party machines.)		

## Attention

- 1.The vinyl temperature needs to be reach 45°C(113°F) to change color.
- 2.Suitable for metal glass, plastic, ceramic, paper, smooth wall.
- 3.Not suitable for uneven surfaces,powdered walls damp walls and object surfaces.
- 4.Not suitable for clothing and other textiles.

## Warm Tips

- 1.Store in a cool and dry area without direct sunlight.
- 2.Do not rinse the vinyl sheet with water within 24 hours after pasting.
- 3.Avoid strong acid and alkali corrosion.

## Customer Service

Feel free to contact us if you have any questions or concerns.

Web: [www.loklik.com](http://www.loklik.com)